



201 Westland Farm Road
P.O. Box 5
Mount Holly, NC 28120
704-827-0216

PRESOAK

SOLVENT DEGREASER

ARROCHEM'S PRESOAK is specifically designed to facilitate in the rapid removal of oils, waxes, greases, tars, gums, fats, and resins from process equipment and other affected surfaces. It can be applied for superior cleaning at ambient temperature without the need for heating of product or applied area. Application of Presoak may be through brushing, soaking, spraying, or wiping. In addition, user may take advantage of the versatility of Presoak through application in vapor degreasing and ultrasonic systems. Product proves especially effective on aluminum surfaces and will not cause surface corrosion unless applied under combinations of heat and pressure. ArroChem recommends use of Presoak as a solvent degreaser for cleaning parts, machinery, hoods, coils, concrete floors, etc.

General Characteristics:

| | |
|---------------------------|--------------------------------|
| Appearance: | Colorless Clear Fluid |
| Chemical Composition: | Oxygenated Hydrocarbon Solvent |
| Solubility in Water, 25C: | GOOD |
| pH, 1% solution: | 7 |
| Foaming Nature: | Non foaming |
| Phosphate Content: | 0 |
| Viscosity: | 10-30 cps (25C, 1 atm) |

Application: *

Presoak can be sprayed, wiped, or brushed onto surface for removal of grease and foreign matter from steel, aluminum, cast iron or other substrates. Presoak contains no water and can be used over a wide range of temperatures. For removal and rinsing, a second application of ArroBrite Presoak to flush surface free of soils, followed by air-drying, should be sufficient for effective cleaning.

*As conditions vary, all dosages and guidelines are merely suggested starting points; it is recommended the user determine the proper operating conditions for his/her system

